

NOTE: This home may require wall bracing tie-downs depending on wind/seismic design. Please refer to the permit set for tie-down loads and locations if applicable. Some areas of the exterior wall sheathing may be shipped loose to allow access for tie-down installation. All tie-down designs are by others.



2M3003-R8 2852 Approx. 1421 Sq. Ft.

 Paddle Fan	 Exterior Light	 Switched Receptacle	 Receptacle
 FLUORADORE DOOR	 Stem Light	 RCA Jack	 HDMI Conduit
	 6" Recessed LED Light	 USB Jack	 HDMI Computer Jack
 24" LIGHT BAR	 4" Recessed LED Light	 COMP	 Computer Jack
	 JB	 Exterior Faucet	 Thermostat

Stairway:
 Riser HT: 8 1/4" Max.
 Tread Depth: 9" Min.
 Head Room: 80" Min.
 Note: The Stairwell geometry in this home has been designed to the criteria above. If IRC geometry is required or desired, please contact Manorwood for plan adjustments.

Builder: Manorwood Homes Title: Literature	Callout: 2852	Revisions: 6/22/2020 3	Scale: 1/8" = 1'-0" Drawn By: JH	Date: 02/25/2020 Reference: NONE	Cust Stock Dir: Village Homes S/N: .	Model/Eng. No.: 2M3003-R8 LIT	
		Date No.		Date: 3/6/2020 1	Reference: NONE	S/N: .	Pg.:
		Date No.		Date: 3/17/2020 2	Reference: NONE	S/N: .	Pg.: